

DANTEC LIMITED
TECHNICAL DATA SHEET

DANOIL VR AG COMPOSITE HOSE

Bore		Max Working		Bend		Weight	
Diameter		Pressure		Radius			
INS	MM	BARS	PSI	INS	MM	KG/M	LB/FT
3	75	7.0	100	4.0	100	2.4	1.6
4	100	7.0	100	5.5	140	3.4	2.3
6	150	7.0	100	7.0	180	8.3	5.6
8	200	7.0	100	8.0	205	12.5	8.4
10	250	7.0	100	11.0	280	16.0	10.7

CONSTRUCTION:-

- 1) Inner Wire Helix : Galvanised Mild Steel High tensile Strength Wire
- 2) Lining : Polypropylene
- 3) Sealing Film : Polypropylene
- 4) Reinforcements : Polypropylene
- 5) Cover : PVC Coated Polyester Cloth
- 6) Outer Wire Helix : Galvanised Mild Steel High Tensile Strength Wire

TEMPERATURE:- : - 20 Deg. C to + 80 Deg. C

SAFETY FACTOR : 4 : 1

N.B. It is important to advise Dantec of the product being conveyed when ordering Composite Hoses.

All hoses supplied have electrical continuity and are tested & certified accordingly.